

# EMME ANTINCENDIO S.r.l. www.emme-italia.com

# 22092-1

### 9 L. Water FIRE EXTINGUISHER



- CYLINDER
   Alloy steel, 3 pieces drawing,
   epoxypolyestere powder painting,
   Red Ral 3000.
- EXTINGUISHING AGENT Water .
- PROPELLANT
   Dehumidified air or N<sub>2</sub>.
- VALVE
   M. 30x1.5, brass body, levers with red painting Ral 3000 .
- USE
   A fire rating (solid materials).
- BRACKET

  Wall-mounted for valve,
  in standard equipment.

WATER DIELECTRIC FIRE EXTINGUISHER Suitable up to 35'000 V. at a distance of 1 mt.

Note: image is for illustrative purpose only, the product purchased can has some differences

9 L. water fire extinguisher, temperature range from +5°C to +60°C, manufactured in accordance to EN 3-7:2008 certified according to the directive for pressure equipment PED 2014/68/EU.

Quality Product certification guaranteed by Bureau Veritas Italia.

Suitable for use on fire involving electrical voltages up to 35 000 V, at a distance of 1 mt.

APPROVED/CERTIFIED FIRE EXTINGUISHER:







<u>FIRE</u> RATING :




### 9 L. Water FIRE EXTINGUISHER

#### **TECHNICAL SPECIFICATIONS**

FIRE RATING	21 A			
EXTINGUISHING AGENT	Water			
PROPELLANT	Dehumidified air or N <sub>2</sub> ,15 Bar at 20°C			
TEMPERATURE RANGE	+5°C / +60°C			
NOMINAL CHARGE	9 L.			
FULL WEIGHT	~ 14 Kg			
DIMENSIONS	Height 635 mm Diameter 170 mm			
DISCHARGE TIME	38 sec.			
VALVE TIGHTENING TORQUE	Minimum 45 Nm, Maximum 68 Nm			
CYLINDER PRESSURE TEST	PT 27 bar			
CYLINDER VOLUME	10,7 L.			
SAFETY VALVE	Set 20 and 26 bar			
CYLINDER MATERIAL	Alloy steel			
EXTERNAL/INTERNAL TREATMENT	Sandblast and epoxypolyestere powder painting, Red Ral 3000 colour/ Internal plastic lining			


#### **PACKAGING**

STANDARD: maximum 40 pieces for pallet (40 pieces for box, max 1 box for pallet)
Pallet dimensions 100x120x80(h) cm



## SINGLE PACKAGING ON REQUEST:


- maximum 40 pieces on pallet 100x120



Note: the packaging quantities and measurements are indicative and can be subject at changes

#### **MAINTENANCE AND INSTALLATION**

For outdoor or marine installation is recommended to protect the fire extinguisher with cover or box. Maintenance according to the rules in use in utilization country.



#### **SPARE PARTS**

NUMBER	DESCRIPTION	CODE
1	Valve M. 30x1.5	0212F
2	Cylinder	0111-1
3	PVC dip tube	0155-1
4	Label	2243-4
5	Hose with dispensing nozzle	0293
6	Safety pin	0282-1
	Safety valve	0261
	Safety pin seal	0285
	Water (9 L. recharge, ready to use)	2055-7

File name	Code	Date	Rele.	Check	Rev.	Pag.
ds_22092-1	22092-1	27/12/17	M.R	MR	1	2

#### **EMME ANTINCENDIO S.r.I**

Via del Molino, 40 - 52010 Corsalone (AR) - Italy info@emme-italia.com - Tel. +39.0575.511320
Others Emme Antincendio s.r.l. warehouses in Italy : Milano - Padova - Reggio Emilia P.IVA/ C.F. 11208251006 - R.E.A. FI-632545