

EMME ANTINCENDIO S.r.l. www.emme-italia.com

22093

9 L. Water + Additive FIRE EXTINGUISHER



- epoxypolyestere powder painting, Red Ral 3000.
- Water foam.
- **PROPELLANT** Dehumidified air or N_2 .
- M. 30x1.5, brass body, levers with red painting Ral 3000.
- A B fire rating
- BRACKET Wall-mounted for valve, in standard equipment.

Note: image is for illustrative purpose only, the product purchased can has some differences

9 L. water + additive fire extinguisher, temperature range from +5°C to +60°C, manufactured in accordance to EN 3-7, approved to European Marine Directive MED 2014/90/EU, S.O.L.A.S. (Safety of life at sea) '74 (2000), certified according to the directive for pressure equipment PED 2014/68/EU.

Quality Product certification guaranteed by Bureau Veritas Italia.

Suitable for use on fire involving electrical voltages up to 1'000 V, at a distance of 1 mt.

AVAILABLE VERSIONS



N.	CODE	DESCRIPTION
1	27093	9 L. water + additive fire extinguisher, complies MED 2014/90/EU

MED version not includes the wall-mounted bracket for valve (see spare parts list at next page)

APPROVED/CERTIFIED FIRE EXTINGUISHER:














9 L. Water + Additive FIRE EXTINGUISHER

TECHNICAL SPECIFICATIONS

FIRE RATING	34 A 233 B		
EXTINGUISHING AGENT	Water + additive EW 6 (AFFF 6 %)		
PROPELLANT	Dehumidified air or N ₂ ,15 Bar at 20°C		
TEMPERATURE RANGE	+5°C / +60°C		
NOMINAL CHARGE	9 L.		
FULL WEIGHT	~ 14 K		
DIMENSIONS	Height 635 mm Diameter 170 mm		
DISCHARGE TIME	34,5 sec.		
VALVE TIGHTENING TORQUE	Minimum 45 Nm, Maximum 68 Nm		
CYLINDER PRESSURE TEST	PT 27 bar		
CYLINDER VOLUME	10,7 L.		
SAFETY VALVE	Set between 20 and 26 bar		
CYLINDER MATERIAL	Alloy steel		
EXTERNAL/INTERNAL TREATMENT	Sandblast and epoxypolyestere powder painting, Red Ral 3000 colour/ Internal plastic lining		


PACKAGING

STANDARD: maximum 40 pieces for pallet (40 pieces for box, max 1 box for pallet) Pallet dimensions 100x120x80(h) cm



SINGLE PACKAGING ON REQUEST:


- maximum 40 pieces on pallet 100x120



Note: the packaging quantities and measurements are indicative and can be subject at changes

MAINTENANCE AND INSTALLATION

For outdoor or marine installation is recommended to protect the fire extinguisher with cover or box. Maintenance according to the rules in use in utilization country.



SPARE PARTS

NUMBER	DESCRIPTION	CODE	
1	Valve M. 30x1.5	0212F	
2	Cylinder	0111-1	
3	PVC dip tube	0155-1	
4	Label 22093	0077	
4	Label 27093	0068	
5	Hose with dispensing nozzle	0293	
6	Safety pin	0282-1	
	Safety valve	0261	
	Safety pin seal	0285	
	Water + additive EW 6 (9 L. recharge, ready to use)	2055	
OPTIONAL	Iron marine bracket red painting	0318-1	

File name	Code	Date	Rele.	Check	Rev.	Pag.
ds_22093	22093	27/12/17	M.R	MR	1	2

EMME ANTINCENDIO S.r.I Via del Molino, 40 - 52010 Corsalone (AR) - Italy info@emme-italia.com - Tel. +39.0575.511320 Others Emme Antincendio s.r.l. warehouses in Italy : Milano - Padova - Reggio Emilia P.IVA/ C.F. 11208251006 - R.E.A. FI-632545