



EMME ANTINCENDIO S.r.l.

www.emme-italia.com

21125-2

## 12 Kg Powder FIRE EXTINGUISHER



- **CYLINDER**  
Alloy steel, 3 pieces drawing, epoxypolyestere powder painting, Red Ral 3000.
- **EXTINGUISHING AGENT**  
ABC Powder - MAP 20 %.
- **PROPELLANT**  
Dehumidified air or N<sub>2</sub>.
- **VALVE**  
M. 30x1.5, brass body, levers with red painting Ral 3000.
- **USE**  
A B C fire rating (solid materials, flammable liquids, flammable gas).
- **BRACKET**  
Wall-mounted for valve, in standard equipment.

© REPRODUCTION IS PROHIBITED

*Note: image is for illustrative purpose only, the product purchased can has some differences*

12 Kg powder fire extinguisher, temperature range from -30°C to +60°C, manufactured in accordance to **EN 3-7:2008**, certified according to the directive for pressure equipment PED 2014/68/EU.

Quality Product certification guaranteed by Bureau Veritas Italia.

Suitable for use on fire involving electrical voltages up to 1'000 V, at a distance of 1 mt.

APPROVED/CERTIFIED FIRE EXTINGUISHER:



**FIRE  
RATING :**



55



233



✓


## 12 Kg Powder FIRE EXTINGUISHER

## TECHNICAL SPECIFICATIONS

FIRE RATING	55 A 233 B C
EXTINGUISHING AGENT	EPW 18462 (ABC Favorit Tertia) ABC powder - MAP 20 %
PROPELLANT	Dehumidified air or N <sub>2</sub> ,15 Bar at 20°C
TEMPERATURE RANGE	-30°C / +60°C
NOMINAL CHARGE	12 Kg
FULL WEIGHT	~ 17,6 Kg
DIMENSIONS	Height 610 mm Diameter 190 mm
DISCHARGE TIME	29,5 sec.
VALVE TIGHTENING TORQUE	Minimum 45 Nm, Maximum 68 Nm
CYLINDER PRESSURE TEST	PT 27 bar
CYLINDER VOLUME	12,5 L.
SAFETY VALVE	Set between 20 and 26 bar
CYLINDER MATERIAL	Alloy steel
EXTERNAL/INTERNAL TREATMENT	Sandblast and epoxypolyestere powder painting, Red Ral 3000 colour

## PACKAGING


STANDARD : maximum 30 pieces for pallet  
(30 pieces for box, max 1 box for pallet)  
Pallet dimensions 100x120x75(h) cm



*Note: the packaging quantities and measurements are indicative and can be subject at changes*

## MAINTENANCE AND INSTALLATION

For outdoor or marine installation is recommended to protect the fire extinguisher with cover or box. Maintenance according to the rules in use in utilization country.



## SPARE PARTS

NUMBER	DESCRIPTION	CODE
1	Valve M. 30x1.5	0212
2	Cylinder	0105
3	PVC dip tube	0155-1
4	Hose	0292-4
5	Label	0059-2
6	Safety pin	0282-1
	Safety valve	0261
	Safety pin seal	0285
	ABC powder - MAP 20 % (12 Kg recharge)	18462-3

File name	Code	Date	Rele.	Check	Rev.	Pag.
ds_21125-2	21125-2	25/10/17	M.R	AA	1	2

## EMME ANTINCENDIO S.r.l

Via del Molino, 40 - 52010 Corsalone (AR) - Italy  
info@emme-italia.com - Tel. +39.0575.511320  
Others Emme Antincendio s.r.l. warehouses in Italy : Milano - Padova - Reggio Emilia  
P.IVA/ C.F. 11208251006 - R.E.A. FI-632545