



EMME ANTINCENDIO S.r.l.

www.emme-italia.com

21031-4

3 Kg Powder FIRE EXTINGUISHER



- **CYLINDER**
Alloy steel, deep drawing, epoxy polyester powder painting, Red Ral 3000.
- **EXTINGUISHING AGENT**
ABC Powder - MAP 40 %.
- **PROPELLANT**
Dehumidified air or N₂.
- **VALVE**
M. 30x1.5, brass body, levers with red painting Ral 3000.
- **USE**
A B C fire rating (solid materials, flammable liquids, flammable gas).

Note: image is for illustrative purpose only, the product purchased can has some differences

3 Kg powder fire extinguisher, temperature range from -20°C to +60°C, manufactured in accordance to **UNI EN 3-7 (D.M. 7.1.2005)**, approved Marine Equipment Directive **MED 2014/90/EU**, certified according to the directive for pressure equipment **PED 2014/68/EU**.

Quality Product certification guaranteed by Bureau Veritas Italia.

Suitable for use on fire involving electrical voltages up to 1'000 V, at a distance of 1 mt.

© REPRODUCTION IS PROHIBITED

APPROVED/CERTIFIED FIRE EXTINGUISHER:



FIRE RATING :



13



113



✓


3 Kg Powder FIRE EXTINGUISHER

TECHNICAL SPECIFICATIONS


FIRE RATING	13 A 113 B C
EXTINGUISHING AGENT	EPB 0351 (QFIRE-40) ABC powder - MAP 40 %
PROPELLANT	Dehumidified air or N ₂ ,15 Bar at 20°C
TEMPERATURE RANGE	-20°C / +60°C
NOMINAL CHARGE	3 Kg
FULL WEIGHT	~ 5,4 Kg
DIMENSIONS	Height(base-valve) 470 mm Diameter 130 mm
DISCHARGE TIME	13,5 sec.
VALVE TIGHTENING TORQUE	Minimum 45 Nm, Maximum 68 Nm
CYLINDER PRESSURE TEST	PT 27 bar
CYLINDER VOLUME	4,3 L.
SAFETY VALVE	Set between 20 and 26 bar
CYLINDER MATERIAL	Alloy steel
EXTERNAL/INTERNAL TREATMENT	Sandblast and epoxypolyestere powder painting, Red Ral 3000 colour

PACKAGING

STANDARD : maximum 126 pieces for pallet
(63 pieces for box, max 2 boxes for pallet)
Pallet dimensions 100x120x115(h) cm




SINGLE PACKAGING
ON REQUEST



Note: the packaging quantities and measurements are indicative and can be subject at changes

MAINTENANCE AND INSTALLATION

For outdoor or marine installation is recommended to protect the fire extinguisher with cover or box. Maintenance according to the rules in use in utilization country.



SPARE PARTS

NUMBER	DESCRIPTION	CODE
1	Valve M. 30x1.5	0212
2	Cylinder	0103
3	PVC dip tube	0153
4	Label	0090
5	Hose	0291
6	Safety pin	0282-1
	Safety valve	0261
	Safety pin seal	0285
OPTIONAL	Iron marine bracket red painting	0315

File name	Code	Date	Rele.	Check	Rev.	Pag.
ds_21031-4	21031-4	03/04/20	M.R	MR	2	2

EMME ANTINCENDIO S.r.l

Via del Molino, 40 - 52010 Corsalone (AR) - Italy
info@emme-italia.com - Tel. +39.0575.511320

Others Emme Antincendio s.r.l. warehouses in Italy : Milano - Padova - Reggio Emilia
P.IVA/ C.F. 11208251006 - R.E.A. FI-632545