

EMME ANTINCENDIO S.r.l. www.emme-italia.com

21063-1

6 Kg Powder FIRE EXTINGUISHER



- CYLINDER Alloy steel, deep drawing, epoxypolyestere powder painting, Red Ral 3000.
- EXTINGUISHING AGENT
- PROPELLANT Dehumidified air or N_2 .
- M. 30x1.5, brass body, levers with red painting Ral 3000.
- USE A B C fire rating (solid materials, flammable liquids, flammable gas).

Note: image is for illustrative purpose only, the product purchased can has some differences

6 Kg powder fire extinguisher, temperature range from -30°C to +60°C, manufactured in accordance to UNI EN 3-7 (D.M. 7.1.2005), approved Marine Equipment Directive MED 2014/90/EU, certified according to the directive for pressure equipment PED 2014/68/EU.

Quality Product certification guaranteed by Bureau Veritas Italia.

Suitable for use on fire involving electrical voltages up to 1'000 V, at a distance of 1 mt.

APPROVED/CERTIFIED FIRE EXTINGUISHER:





























6 Kg Powder FIRE EXTINGUISHER


TECHNICAL SPECIFICATIONS

FIRE RATING	34 A 233 B C			
EXTINGUISHING AGENT	EPW 18462 (ABC Favorit Tertia) ABC powder - MAP 20 %			
PROPELLANT	Dehumidified air or N ₂ ,15 Bar at 20°C			
TEMPERATURE RANGE	-30°C / +60°C			
NOMINAL CHARGE	6 Kg			
FULL WEIGHT	~ 9,4 Kg			
DIMENSIONS	Height(base-valve) 540 mm Diameter 160 mm			
DISCHARGE TIME	23 sec.			
VALVE TIGHTENING TORQUE	Minimum 45 Nm, Maximum 68 Nm			
CYLINDER PRESSURE TEST	PT 27 bar			
CYLINDER VOLUME	7,8 L.			
SAFETY VALVE	Set between 20 and 26 bar			
CYLINDER MATERIAL	Alloy steel			
EXTERNAL/INTERNAL TREATMENT	Sandblast and epoxypolyestere powder painting, Red Ral 3000 colour			

PACKAGING

STANDARD: maximum 100 pieces for pallet (44 pieces for box, max 2 boxes for pallet) (12 pieces in single packaging)


Pallet dimensions 100x120x160(h) cm



SINGLE PACKAGING ON REQUEST:


- maximum 64 pieces on pallet 100x120 cm
- maximum 48 pieces on pallet 80x120 cm

Note: the packaging quantities and measurements are indicative and can be subject at changes



MAINTENANCE AND INSTALLATION

For outdoor or marine installation is recommended to protect the fire extinguisher with cover or box. Maintenance according to the rules in use in utilization country.



SPARE PARTS

NUMBER	DESCRIPTION	CODE
1	Valve M. 30x1.5	0212
2	Cylinder	0104
3	PVC dip tube	0154
4	Hose	0292
5	Label	0054-1
6	Safety pin	0282-1
	Safety valve	0261
	Safety pin seal	0285
OPTIONAL	Iron marine bracket red painting	0316
OPTIONAL	Stainless steel marine bracket	1464

File name	Code	Date	Rele.	Check	Rev.	Pag.
ds_21063-1	21063-1	03/04/20	M.R	MR	2	2

EMME ANTINCENDIO S.r.l

Via del Molino, 40 - 52010 Corsalone (AR) - Italy info@emme-italia.com - Tel. +39.0575.511320
Others Emme Antincendio s.r.l. warehouses in Italy : Milano - Padova - Reggio Emilia P.IVA/ C.F. 11208251006 - R.E.A. FI-632545