



EMME ANTINCENDIO S.r.l.  
www.emme-italia.com

25069

## 6 Kg D Powder FIRE EXTINGUISHER



- **CYLINDER**  
Alloy steel, 3 pieces drawing, epoxypolyestere powder painting, Red Ral 3000.
- **EXTINGUISHING AGENT**  
D powder .
- **PROPELLANT**  
Dehumidified air or N<sub>2</sub> .
- **VALVE**  
CPF M. 30x1.5, brass body, levers with red painting Ral 3000.
- **USE**  
D fire rating  
(recommended in environments with risks arising from the presence of flammable metal).

*Note: image is for illustrative purpose only, the product purchased can has some differences*

6 Kg powder fire extinguisher, temperature range from -30°C to +60°C, manufactured in accordance to **UNI EN 3-7**, certified according to the directive for pressure equipment PED 2014/68/EU.

Quality Product certification guaranteed by Bureau Veritas Italia.

Suitable for use on fire involving electrical voltages up to 1'000 V, at a distance of 1 mt.

APPROVED/CERTIFIED FIRE EXTINGUISHER:



**FIRE  
RATING :**



# 25069


## 6 Kg D Powder FIRE EXTINGUISHER

### TECHNICAL SPECIFICATIONS

FIRE RATING	D
EXTINGUISHING AGENT	EPD 0356 (PRO-M) - D powder
PROPELLANT	Dehumidified air or N <sub>2</sub> ,15 Bar at 20°C
TEMPERATURE RANGE	-30°C / +60°C
NOMINAL CHARGE	6 Kg
FULL WEIGHT	~ 10 Kg
DIMENSIONS	Height(base-valve) 505 mm Diameter 160 mm
DISCHARGE TIME	18,5 sec.
VALVE TIGHTENING TORQUE	Minimum 45 Nm, Maximum 68 Nm
CYLINDER PRESSURE TEST	PT 27 bar
CYLINDER VOLUME	7,3 L.
SAFETY VALVE	Set between 20 and 24 bar
CYLINDER MATERIAL	Alloy steel
EXTERNAL/INTERNAL TREATMENT	Sandblast and epoxypolyestere powder painting, Red Ral 3000 colour


### PACKAGING

STANDARD : maximum 100 pieces for pallet  
(44 pieces for box, max 2 boxes for pallet)  
(12 pieces in single packaging)  
Pallet dimensions 100x120x160(h) cm



SINGLE PACKAGING  
ON REQUEST:


- maximum 64 pieces on pallet 100x120 cm
- maximum 48 pieces on pallet 80x120 cm



*Note: the packaging quantities and measurements are indicative and can be subject at changes*

### MAINTENANCE AND INSTALLATION

For outdoor or marine installation is recommended to protect the fire extinguisher with cover or box. Maintenance according to the rules in use in utilization country.



### SPARE PARTS

NUMBER	DESCRIPTION	CODE
1	Valve M. 30x1.5	0212C
2	Cylinder	1848K
3	PVC dip tube	1859
4	Hose	SL0293
5	Extension hose	1778-2
6	Horn	2259-41
7	Magnet stop hose	0301-1
8	Label	1943
9	Safety pin	0282C
	Safety valve	0261C
	Safety pin seal	0285

File name	Code	Date	Rele.	Check	Rev.	Pag.
ds_25069	25069	06/04/20	M.R	MR	2	2

### EMME ANTINCENDIO S.r.l

Via del Molino, 40 - 52010 Corsalone (AR) - Italy  
info@emme-italia.com - Tel. +39.0575.511320

Others Emme Antincendio s.r.l. warehouses in Italy : Milano - Padova - Reggio Emilia  
P.IVA/ C.F. 11208251006 - R.E.A. FI-632545