

EMME ANTINCENDIO S.r.l. www.emme-italia.com

17103-1

10kg CO₂ WHEELED FIRE EXTINGUISHER



- epoxypolyestere powder painting, Red Ral 3000.
- **EXTINGUISHING AGENT** Carbon Dioxide 99,99%
- VALVE M. 25x2, brass body, red painting Ral 3000, with protection for valve.
- B fire rating (flammable liquids)
- BRACKET Chassis on wheels, red painting Ral 3000.

Note: image is for illustrative purpose only, the product purchased can has some differences

10kg CO₂ wheeled fire extinguisher, temperature range from -30°C to +60°C, manufactured in accordance to EN 1866-1, approved to European Marine Directive MED 2014/90/EU, S.O.L.A.S. (Safety of life at sea) '74 (2000), certified according to the directive for pressure equipment PED 2014/68/EU.

Quality Product certification guaranteed by Bureau Veritas Italia.

Suitable for use on fire involving electrical voltages up to 1000 V, at a distance of 1 mt.

AVAILABLE VERSIONS

N.	CODE	DESCRIPTION
1	14103-1	10kg CO ₂ fire extinguisher, complies MED 2014/90/EU

APPROVED/CERTIFIED FIRE EXTINGUISHER:
















10kg CO₂ WHEELED FIRE EXTINGUISHER

TECHNICAL SPECIFICATIONS

FIRE RATING	144 B
EXTINGUISHING AGENT	CO ₂ 99,99%
TEMPERATURE RANGE	-30°C +60°C
NOMINAL CHARGE	10 Kg
FULL WEIGHT	~ 36 Kg
DIMENSIONS	Height 940 mm Width 430 mm Depth 480 mm
DISCHARGE TIME	16 sec.
VALVE TIGHTENING TORQUE	Minimum 95 Nm, Maximum 130 Nm
CYLINDER PRESSURE TEST	PT 250 bar
CYLINDER VOLUME	7,5 L. x 2
SAFETY VALVE	Set 195 +/- 10 bar
CYLINDER MATERIAL	Alloy steel
EXTERNAL/INTERNAL TREATMENT	Sandblast and epoxypolyestere poweder painting, Red Ral 3000 colour

PACKAGING


STANDARD: maximum 6 pieces for pallet Pallet dimensions 100x120x110(h) cm



Note: the packaging quantities and measurements are indicative and can be subject at changes

MAINTENANCE AND INSTALLATION

For outdoor or marine installation is recommended to protect the fire extinguisher with cover. Maintenance according to the norm in use in utilization country.



SPARE PARTS

NUMBER	DESCRIPTION	CODE
1	Valve M. 25x2	0222-3
2	Cylinder	0110-1
3	PVC dip tube	0160-3
4	Hose sae 100 R1 T1/2"	1828
5	Dispensing nozzle (complete of ball valve with control lever)	0336
6	Chassis	18488
7	Wheel + wheel stop (diam. 300mm)	0124
8	Label 17103-1	18383
8	Label 14103-1	18383M
9	Safety pin	0284
10	Valve protection	8623-1

File name Code Date Rele. Check Rev. Pag. ds_17103-1 17103-1 24/04/19 M.R 2 2

EMME ANTINCENDIO S.r.l Via del Molino, 40 - 52010 Corsalone (AR) - Italy

via dei Molinio, 40 - 32010 Corsanio (An) - Italy info@emme-italia.com - Tel. +39.0575.511320 Others Emme Antincendio s.r.l. warehouses in Italy : Milano - Padova - Reggio Emilia P.IVA/ C.F. 11208251006 - R.E.A. FI-632545