



PRODUZIONE ESTINTORI D'INCENDIO OMOLOGATI E CERTIFICATI
PRODUCTION OF APPROVED FIRE EXTINGUISHERS

www.emme-italia.com



Data Sheet

Code 18118 Kg 100 Powder Wheeled Fire Extinguisher EN 1866-1
Code 16118 Approved European Marine Equipment Directive (MED 96/98/CE)
Fire Rating A IV B C



Features

- Manufactured in accordance with and tested EN 1866-1.
- Approved to European Marine Directive MED 96/98/CE
- S.O.L.A.S. (Safety of life at sea) '74 (2000)
- CE Marked according to Directive PED 2014/68/EU
- *Quality Product* certification guaranteed by Bureau Veritas Italia
- Permanent pressure with N2 or dehumidified air
- EPW 18462 Powder

The powder is not conductive and the fire extinguisher may be used in presence of electric equipment up to 1000V.

ABC Powder is ideal for Class A fires (solid combustibles), Class B fires (flammable liquids) and Class C fires (flammable gases).

- Manufactured in Italy



File Name	Code	Date	Ceck	Rev.	Pag.
DS_18118_1822 1.Docx	18118	16/08/2016	M.P.	0	1/2

EMME ANTINCENDIO S.r.l

Factory: Via del Molino, 40 - 52010 Corsalone (AR) - Italy - Tel. +39.0575.511320
Warehouse: Via G. Di Vittorio, 11 - 20017 Mazzo di Rho (MI) - Italy - Tel. +39.0293900399
E-mail: info@emme-italia.com - milano@emme-italia.com - web site: www.emme-italia.com
P.IVA/ C.F. 11208251006 - R.E.A. FI-632545 -



PRODUZIONE ESTINTORI D'INCENDIO OMOLOGATI E CERTIFICATI
PRODUCTION OF APPROVED FIRE EXTINGUISHERS

www.emme-italia.com



Technical Specifications

Model EN 1866-1	<i>cod. 18118</i>
Model MED 96/98CE	<i>cod. 16118</i>
Fire Rating	<i>A IV B C</i>
Extinguishing Agent	<i>EPW 18462 Powder</i>
Temperature Range	<i>-30°C + 60°C</i>
Working Pressure	<i>Dehumidified air or N2 14 Bar a 20°C</i>
Nominal Charge	<i>Kg 100</i>
Cylinder Volume	<i>L 130</i>
Discharge Range	<i>100 sec.</i>
Discharge Range	<i>10 m</i>
Hose	<i>EPDM m 10</i>
Cylinder Pressure Test	<i>PT 30 Bar</i>
Cylinder Material	<i>Carbon Steel EN10111</i>
External Treatment	<i>Sandblast, epoxypolyestere coating red RAL 3000</i>

Discharge Valve *Brass 2"*
Safety Valve *22 +/- 2 Bar*

Dimensions

Height 1300 mm
Width 580 mm
Depth 550 mm
Full weight Kg 165
Packaging 80x120x145cm 2pcs.

Installation

Do not expose the fire extinguisher to direct sunlight.
A protective Pvc cover is recommended when installed in marine and off-shore environments


Spare Parts List

Pos.	Description	Code
1	Valve	0214
1	Pressure Gauge	1576
2	Hose	18422
3	Nozzle	18441
4	EPW 18462 powder	18462
5	Wheel d. 400 mm	0125

Optional

Cover pvc

Code 1796



Maintenance

The extinguishers must be inspected and serviced by a TRAINED QUALIFIED PERSON in accordance with the local regulation concerning the inspections of the pressure equipments fire extinguishers. To ensure safe, trouble free performance and long life of the extinguishers, the manufacturer recommends the following: At least every two years replace the extinguishing agent; Inspect the cylinder and valve assembly for any external and internal damage or corrosion. Repair or replace all defective parts using only Manufacturers supplied parts or refills; At least every 12 years from date of manufacture the extinguisher must be overhauled by means of an hydraulic pressure test at the pressure PT stamped on the cylinder, and submitted to a thorough inspection of the cylinder and valve should be made checking for any external or internal damage or corrosion. Any defective parts should be repaired or replaced using the specified parts mentioned in the spare part list.

File Name	Code	Date	Ceck	Rev.	Pag.
DS_18118_1822 1.Docx	18118	16/08/2016	M.P.	0	2/2

EMME ANTINCENDIO S.r.l

Factory: Via del Molino, 40 - 52010 Corsalone (AR) - Italy - Tel. +39.0575.511320
Warehouse: Via G. Di Vittorio, 11 - 20017 Mazzo di Rho (MI) - Italy - Tel. +39.0293900399
E-mail: info@emme-italia.com - milano@emme-italia.com - web site: www.emme-italia.com
P.IVA/ C.F. 11208251006 - R.E.A. FI-632545 -