

Technical Manual



www.emme-italia.com

Via del Molino, 40 – 52010 Corsalone (AR) – Italy – info@emme-italia.com – Tel. +39.0575.511320
P.IVA/ C.F. 11208251006 – R.E.A. AR-159122

17204-20 Any Wave 20 : Wheeled Fire Extinguisher, 20 Kg Carbon Dioxide




Note: image is for illustrative purpose only, the product purchased can has some difference

- **CYLINDER**
Alloy steel, external powder painting, color Red Ral 3000.
- **EXTINGUISHING AGENT**
Carbon Dioxide 99,99 % (CO₂) .
- **VALVE**
W 28.8, brass body, handwheel red painting, with protection for valve.
- **USE**
Fire Rating class B (flammable liquids).
- **BRACKET**
Frame on wheels, red painting Ral 3000.

REPRODUCTION IS PROHIBITED

20 Kg Carbon Dioxide Fire Extinguisher, temperature range from -30°C to +60°C, manufactured in accordance to **UNI EN 1866-1**, approved Marine Equipment Directive **MED 2014/90/UE**, certified according to the directive for pressure equipment **PED 2014/68/EU**. Quality Product certification guaranteed by Bureau Veritas Italia. Suitable for use on fire involving electrical voltages up to 1'000 V, at a minimum distance of 1 meter.

APPROVED/CERTIFIED FIRE EXTINGUISHER:
ESTINTORE APPROVATO/CERTIFICATO:



**FIRE
RATING :**



233

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
17204-20_Technical manual	Technical manual	17204-20 Any Wave 20	15/10/2025	S.R		0	1/3

17204-20 Any Wave 20 : Wheeled Fire Extinguisher, 20 Kg Carbon Dioxide

- **INSTALLATION** The installation must be carried out in accordance with the provisions in force in the country where the device is used. The commissioning and maintenance activities for maintaining efficiency must be carried out in accordance with the document **ECC_1_ENG** by qualified
 - **USE**
 - **MAINTENANCE** technical personnel and in compliance with the regulations in force in the country of use.
- Any tampering or intervention carried out by unqualified personnel will void the product warranty.
It is recommended to place the device in a dry place protected from atmospheric agents.


TECHNICAL SPECIFICATIONS

FIRE RATING	233 B
EXTINGUISHING AGENT	Carbon Dioxide 99,99 % (CO ₂)
TEMPERATURE RANGE	-30°C / +60°C
NOMINAL CHARGE	20 Kg
FULL WEIGHT	~ 64 Kg
FRAME WEIGHT	~ 8,20 Kg (with wheels)
DIMENSIONS	Height 1100 +/- 10 mm Width 485 +/- 10 mm Depth (max size) 460 +/- 10 mm
DISCHARGE TIME	~ 38,2 seconds
CYLINDER PRESSURE TEST	PT 300 bar
CYLINDER VOLUME	28,6 L
SAFETY DEVICE	Set between 230 and 245 bar
CYLINDER MATERIAL	Steel alloy
TREATMENT	Outside: Sandblast and powder painting, Ral 3000

PACKAGING

(Note: quantities and measurements are indicative and can be subject at changes)

STANDARD
Maximum nr. 6 pieces for pallet
Pallet dimensions 100x120x120(h) cm




TRANSPORT DISPOSAL

Land transport : Exemption for the purposes of ADR disposal 594
Ship Transport : IMDG Code – UN 1044 class 2.2 Fire Extinguishers

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
17204_Technical manual	Technical manual	17204 Lazio 18281	27/05/2025	S.R		3	2/3

17204-20 Any Wave 20 : Wheeled Fire Extinguisher, 20 Kg Carbon Dioxide

COMPONENTS AND SPARE PARTS LIST



NUM.	DESCRIPTION	CODE
1	Handwheel valve W 28.8	11531
1.1	Safety pin	0282-1
1.2	Safety device	n.a.
2	Safety pin seal	0285
3	Dip tube aluminum alloy	0166-1
4	Cylinder	18332
5	Hose	18425

NUM.	DESCRIPTION	CODE
6	Dispensing nozzle (complete of ball valve with control lever)	0336
7	Nylon gasket	0204
8	Frame	0123-2
9	Wheel + stopwheel (diam. 300mm)	0124
10	Label 17204	18384-20

The spare part at number 1 includes already others components 1.1 and 1.2

"n.a." mean that the component is not available as single spare part

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
17204-20_Technical manual	Technical manual	17204-20 Any Wave 20	15/10/2025	S.R		0	3/3