

# Technical Manual



www.emme-italia.com

Via del Molino, 40 – 52010 Corsalone (AR) – Italy – info@emme-italia.com – Tel. +39.0575.511320  
P.IVA/ C.F. 11208251006 – R.E.A. AR-159122

## 17304 – Lazio 18282 : Wheeled Fire Extinguisher, 30 Kg Carbon Dioxide



*Note: image is for illustrative purpose only, the product purchased can has some difference*

- **CYLINDER**  
Alloy steel, external powder painting, color Red Ral 3000.
- **EXTINGUISHING AGENT**  
Carbon Dioxide 99,99 % (CO<sub>2</sub>) .
- **VALVE**  
W 28.8, brass body, handwheel red painting, with protection for valve.
- **USE**  
Fire Rating class B (flammable liquids).
- **BRACKET**  
Frame on wheels, red painting Ral 3000.

REPRODUCTION IS PROHIBITED

30 Kg Carbon Dioxide Fire Extinguisher, temperature range from -30°C to +60°C, manufactured in accordance to **UNI EN 1866-1 (D.M. 6.3.92)**, certified according to the directive for pressure equipment PED 2014/68/EU.

Quality Product certification guaranteed by Bureau Veritas Italia.

Suitable for use on fire involving electrical voltages up to 1'000 V, at a minimum distance of 1 meter.


APPROVED/CERTIFIED FIRE EXTINGUISHER:



PED 2014/68/UE

BUREAU VERITAS

For certified MED 2014/90/EU  
version : cod. 14304



**FIRE  
RATING :**



233

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
17304_Technical manual	Technical manual	17304 Lazio 18282	27/05/2025	S.R		3	1/3

# 17304 – Lazio 18282 : Wheeled Fire Extinguisher, 30 Kg Carbon Dioxide

## • INSTALLATION

The installation must be carried out in accordance with the provisions in force in the country where the device is used.

## • USE

The commissioning and maintenance activities for maintaining efficiency must be carried out in accordance with the document **ECC\_1\_ENG** by qualified technical personnel and in compliance with the regulations in force in the country of use.

## • MAINTENANCE

Any tampering or intervention carried out by unqualified personnel will void the product warranty.

It is recommended to place the device in a dry place protected from atmospheric agents.

## TECHNICAL SPECIFICATIONS


FIRE RATING	233 B
EXTINGUISHING AGENT	Carbon Dioxide 99,99 % (CO <sub>2</sub> )
TEMPERATURE RANGE	-30°C / +60°C
NOMINAL CHARGE	30 Kg
FULL WEIGHT	~ 84 Kg
FRAME WEIGHT	~ 8,20 Kg (with wheels)
DIMENSIONS	Height 1320 +/- 10 mm Width 485 +/- 10 mm Depth (max size) 440 +/- 10 mm
DISCHARGE TIME	~ 28,6 seconds
CYLINDER PRESSURE TEST	PT 300 bar
CYLINDER VOLUME	40 L + 5%
SAFETY DEVICE	Set between 230 and 245 bar
CYLINDER MATERIAL	Steel alloy
TREATMENT	Outside: Sandblast and powder painting, Ral 3000

## PACKAGING

(Note: quantities and measurements are indicative and can be subject at changes)

### STANDARD

Maximum nr. 6 pieces for pallet  
Pallet dimensions 100x120x145(h) cm




## TRANSPORT DISPOSAL

Land transport : Exemption for the purposes of ADR disposal 594  
Ship Transport : IMDG Code – UN 1044 class 2.2 Fire Extinguishers

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
17304_Technical manual	Technical manual	17304 Lazio 18282	27/05/2025	S.R		3	2/3

# 17304 – Lazio 18282 : Wheeled Fire Extinguisher, 30 Kg Carbon Dioxide

## COMPONENTS AND SPARE PARTS LIST



NUM.	DESCRIPTION	CODE
1	Handwheel valve W 28.8	11531
1.1	Safety pin	0282-1
1.2	Safety device	n.a.
2	Safety pin seal	0285
3	Dip tube aluminum alloy	0167-1
4	Cylinder	18299
5	Protective cap for valve	0096

NUM.	DESCRIPTION	CODE
6	Hose	18425
7	Dispensing nozzle (complete of ball valve with control lever)	0336
8	Nylon gasket	0204
9	Frame	0123
10	Wheel + stopwheel (diam. 300mm)	0124
11	Label 17304	18385
	Label 14304	18385M

The spare part at number 1 includes already others components 1.1 and 1.2

"n.a." mean that the component is not available as single spare part

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
17304_Technical manual	Technical manual	17304 Lazio 18282	27/05/2025	S.R		3	3/3