

Technical Manual



www.emme-italia.com

Via del Molino, 40 - 52010 Corsalone (AR) - Italy - info@emme-italia.com - Tel. +39.0575.511320
P.IVA/ C.F. 11208251006 - R.E.A. AR-159122

GW50A 19508-701L : Wheeled Fire Extinguisher, 50 L Foam

EXTINGUISHING AGENT SUITABLE FOR LITHIUM BATTERIES



FLUORINE FREE




DISPENSING PISTOL WITH
ROTATING CONNECTION

- CYLINDER
Stainless steel AISI 304,
powder painting, Red Ral 3000.
- EXTINGUISHING AGENT
Fluorine free foam, water based.
- PROPELLANT
Auxiliary pressure.
Fire extinguisher pressurized at
moment of use with Nitrogen (N₂).
- CAP
2"-F, brass.
- USE
A B fire rating
(solid materials, flammable liquids).
- BRACKET
Chassis on wheels, welded at the
cylinder, red painting Ral 3000.
- DISPENSING PISTOL
Body in plastic material.
The rotating connection allow an easy
unroll of hose.

Note: image is for illustrative purpose only, the product purchased can have some differences

50 L foam wheeled fire extinguisher, pressurized at moment of use, temperature range from +5°C to +60°C, manufactured in accordance to **UNI EN 1866-1**, approved Marine Equipment Directive **MED 2014/90/UE**, certified according to the directive for pressure equipment **PED 2014/68/EU**. Quality Product certification guaranteed by Bureau Veritas Italia. Suitable for use on fire involving electrical voltages up to 1'000 V, at a distance of 1 meter.

APPROVED/CERTIFIED FIRE EXTINGUISHER:



FIRE
RATING :



File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
19508-701L_GW50A_ Technical Manual	Technical Manual	GW50A_19508-701L	18/02/2026	S.R.		0	1/4

REPRODUCTION IS PROHIBITED

GW50A 19508-701L : Wheeled Fire Extinguisher, 50 L Foam

- **INSTALLATION** The installation must be carried out in accordance with the provisions in force in the country where the device is used. The commissioning and maintenance activities for maintaining efficiency must be carried out in accordance with the document **CSA_1-B_ENG** by qualified
 - **USE**
 - **MAINTENANCE** technical personnel and in compliance with the regulations in force in the country of use.
- Any tampering or intervention carried out by unqualified personnel will void the product warranty.
It is recommended to place the device in a dry place protected from atmospheric agents.


TECHNICAL SPECIFICATIONS

FIRE RATING	A IV B
EXTINGUISHING AGENT	100% Green Wave Premix Lith-M
PROPELLANT	Nitrogen (N ₂), 100 Bar
TEMPERATURE RANGE	+5°C / +60°C
NOMINAL CHARGE	50 Liters
FULL WEIGHT	~ 80 Kg
DIMENSIONS	Height 1100 +/- 10 mm ; Width 490 +/- 10 mm Depth 560 +/- 15 mm
DISCHARGE TIME	~ 310 seconds
CYLINDER PRESSURE TEST	PT 30 bar
CYLINDER VOLUME	62 L
SAFETY DEVICE	Set between 21 and 26 bar
CYLINDER MATERIAL	Stainless steel AISI 304
TREATMENT	Outside: Sandblast and powder painting Ral 3000

PACKAGING

(Note: the packaging quantities and measurements are indicative and can be subject at change)

STANDARD
Maximum nr. 4 pieces for pallet
Pallet dimensions 100x120x135(h) cm




TRANSPORT DISPOSAL

Land transport : Exemption for the purposes of ADR disposal 594
Ship Transport : IMDG Code – UN 1044 class 2.2 Fire Extinguishers

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
19508-701L_GW50A_Technical Manual	Technical Manual	GW50A_19508-701L	18/02/2026	S.R.		0	2/4

COMPONENTS AND SPARE PARTS LIST



NUM.	DESCRIPTION	CODE
1	2" brass cap	18463
1.1	O-ring cap	n.a.
1.2	Safety device	n.a.
2	Cylinder	18307
3	Hose	18421-5
4	Dispensing pistol	2181-4
5	Dispensing nozzle	1645-5
6	Membrane	0262-4
7	Copper washer	2148-11
8	Complete pressurization cylinder, with Nitrogen	18516-2

NUM.	DESCRIPTION	CODE
8.1	Tilting valve W28.8 x 1/14" for nitrogen cylinder	0223L
8.2	Safety device	n.a.
8.3	Safety pin	0282-1
8.4	Safety pin seal	0285
9	Fitting for cylinder with nitrogen cylinder	18489
10	Fitting for nitrogen cylinder with cylinder	18495
11	Wheel + stop wheel (diam. 300mm)	0124V
12	Label	18376-71L

The spare part at number 1 (valve) includes already others components 1.1 and 1.2
The spare part at number 8 (cylinder) includes already others components indicated from 8.1 to 8.4
"n.a." mean that the component is not available as single spare part.

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
19508-701L_GW50A_ Technical Manual	Technical Manual	GW50A_19508-701L	18/02/2026	S.R.		0	3/4

Prerequisite when using the fire extinguisher on lithium batteries

According to tests executed with this fire extinguisher, it's possible to stop the combustion of a lithium-ion battery with a water based fire extinguisher with foam additives. It has been verified that the use of the fire extinguisher allows to lower the temperature and control any re-ignitions of the cells present inside the battery (generated by the chain reaction of the same and due to their shape inside the battery pack). The fire extinguisher is therefore effective in containing the flames emanated from a battery with same or inferior characteristics compared to the one tested.

**NOTE: the test was executed on a new battery and so at full efficiency.*

SAFETY WARNING



The combustion of lithium-ion batteries releases very harmful gases and fumes. Direct exposure to high concentrations of gases emanating from the combustion of lithium-ion batteries can cause serious damage to health. Lithium-ion batteries can have unpredictable phenomena during fire, such as explosive reactions caused by the pressure of the cells inside the battery pack. It's advisable to use appropriate safety devices. The use of fire extinguisher is recommended for professional and expert staff. The use of fire extinguisher by uninformed people can lead to lower results and cause damage to involved people.

DISCLAIMER

The result of the tests performed refers exclusively to the fire extinguisher model used during the tests themselves. The fast development of lithium-ion batteries and fire extinguishers means that the performance achieved during the test phase is not guaranteed when using lithium-ion batteries or shutdown techniques other than those tested. It is not possible to understand where and to what extent these fire extinguishers can be installed due to the outer casing of the lithium-ion battery pack.

The fire extinguishers tested are intended to help contain the principle of fire resulting from the triggering of a lithium-ion battery.

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
19508-701L_GW50A_ Technical Manual	Technical Manual	GW50A_19508-701L	18/02/2026	S.R.		0	4/4