

Technical Manual



SAFETY
FOR
FUTURE



www.emme-italia.com

Via del Molino, 40 – 52010 Corsalone (AR) – Italy – info@emme-italia.com – Tel. +39.0575.511320
P.IVA/ C.F. 11208251006 – R.E.A. AR-159122

23058-3 : Portable Fire Extinguisher, 5 Kg Carbon Dioxide



OPTIONAL
Adapter with clip



- CYLINDER
Alloy steel, external powder coating, color Red Ral 3000.
- EXTINGUISHING AGENT
Carbon Dioxide 99,99 % (CO₂) .
- VALVE
CPF M. 25x2, brass body, lever red RAL 3000.
- USE
Fire Rating class B (flammable liquids).

Note: image is for illustrative purpose only, the product purchased can has some difference

5 Kg Carbon Dioxide Fire Extinguisher, temperature range from -30°C to +60°C, manufactured in accordance to **UNI EN 3-7 (D.M. 7.1.2005)**, approved by Marine Equipment Directive **MED 2014/90/EU**, certified according to the directive for pressure equipment PED 2014/68/EU. Manufactured according at productions checks as agreed with **EN 3-10**. Quality Product certification guaranteed by Bureau Veritas Italia.
Suitable for use on fire involving electrical voltages up to 1'000 V, at a minimum distance of 1 meter.

APPROVED/CERTIFIED FIRE EXTINGUISHER:



FIRE
RATING :



89

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
23058-3_Technical manual	Technical manual	23058-3	27/05/2025	S.R		3	1/3

REPRODUCTION IS PROHIBITED

23058-3 : Portable Fire Extinguisher, 5 Kg Carbon Dioxide

• INSTALLATION

The installation must be carried out in accordance with the provisions in force in the country where the device is used.

• USE

The commissioning and maintenance activities for maintaining efficiency must be carried out in accordance with the document **EPC_1_ENG** by qualified technical personnel and in compliance with the regulations in force in the country of use.

• MAINTENANCE

Any tampering or intervention carried out by unqualified personnel will void the product warranty.

It is recommended to place the device in a dry place protected from atmospheric agents.

TECHNICAL SPECIFICATIONS


FIRE RATING	89 B
EXTINGUISHING AGENT	Carbon Dioxide 99,99 % (CO ₂)
TEMPERATURE RANGE	-30°C / +60°C
NOMINAL CHARGE	5 Kg
FULL WEIGHT	~ 14,1 Kg
DIMENSIONS	Height (base - valve) 750 +/- 10 mm Diameter (cylinder) 136 +/- 2 mm
DISCHARGE TIME	~ 10 seconds
CYLINDER PRESSURE TEST	PT 250 bar
CYLINDER VOLUME	7,5 L
SAFETY DEVICE	Set at 195 +15/-23 bar
CYLINDER MATERIAL	Alloy steel
TREATMENT	Outside: Sandblast and powder painting, Ral 3000

PACKAGING


(Note: quantities and measurements are indicative and can be subject at changes)

STANDARD

Maximum nr. 65 pieces for pallet
(65 pieces for box, 1 box for pallet)
Pallet dimensions 100x120x100(h) cm



ON REQUEST: SINGLE PACKAGING




TRANSPORT DISPOSAL

Land transport : Exemption for the purposes of ADR disposal 594
Ship Transport : IMDG Code – UN 1044 class 2.2 Fire Extinguishers

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
23058-3_Technical manual	Technical manual	23058-3	27/05/2025	S.R		3	2/3

23058-3 : Portable Fire Extinguisher, 5 Kg Carbon Dioxide

COMPONENTS AND SPARE PARTS LIST



NUM.	DESCRIPTION	CODE
1	Valve M. 25x2	0213C-1
1.1	O-ring valve	0202
1.2	Valve stem	0243C
1.3	Safety device	0262C
1.4	Internal spring of the valve	n.a.
1.5	Dip tube holder	n.a.
2	Safety pin	0282-1
3	Safety pin seal	0285
4	Aluminum dip tube	0160-1

NUM.	DESCRIPTION	CODE
5	Cylinder	0110-1
6	Hose SAE 100 R1 T ½" with dispensing horn Europe model	0332-1
7	Gasket in nylon	0204
8	Label	2254-1
OPTIONAL	Iron ring wall-mounted, red painting, adapter with clip	1907-2
OPTIONAL	Iron marine bracket red painting	0319

The spare part at number 1 includes already all others components indicated from 1.1 to 1.5

"n.a." mean that the component is not available as single spare part

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
23058-3_Technical manual	Technical manual	23058-3	27/05/2025	S.R		3	3/3

REPRODUCTION IS PROHIBITED