

Technical Manual



SAFETY
FOR
FUTURE



www.emme-italia.com

Via del Molino, 40 – 52010 Corsalone (AR) – Italy – info@emme-italia.com – Tel. +39.0575.511320
P.IVA/ C.F. 11208251006 – R.E.A. AR-159122

GW9A 32093-601 : Portable Fire Extinguisher, 9 L Foam



FLUORINE FREE

CLIP DETAIL



- **CYLINDER**
In high-strength alloy steel, with clip, deep drawing, external powder painting Red Ral 3000.
- **EXTINGUISHING AGENT**
Fluorine free foam, water based.
- **PROPELLANT**
Auxiliary pressure.
Fire extinguisher pressurized at moment of use with 80g CO₂ cartridge.
- **VALVE**
M. 74x2, lightweight aluminum alloy, activation with percussion method .
- **USE**
A B fire rating
(solid materials, flammable liquids).

REPRODUCTION IS PROHIBITED

Note: image is for illustrative purpose only, the product purchased can has some difference

9 L foam fire extinguisher, auxiliary pressure, temperature range from +5°C to +60°C, manufactured in accordance to **UNI EN 3-7**, approved Marine Equipment Directive **MED 2014/90/EU**, certified according to the directive for pressure equipment PED 2014/68/EU. Manufactured according at productions checks as agreed with **EN 3-10**. Quality Product certification guaranteed by Bureau Veritas Italia.
Suitable for use on fire involving electrical voltages up to 1'000 V, at a minimum distance of 1 meter.

APPROVED/CERTIFIED FIRE EXTINGUISHER:



**FIRE
RATING :**



34

183

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
32093-601_GW9A_Technical manual	Technical manual	GW9A_32093-601	08/10/25	S.R.		0	1/3

GW9A 32093-601 : Portable Fire Extinguisher, 9 L Foam

- **INSTALLATION** The installation must be carried out in accordance with the provisions in force in the country where the device is used. The commissioning and maintenance activities for maintaining efficiency must be carried out in accordance with the document **PSA_1_ENG** by qualified
- **USE**
- **MAINTENANCE** technical personnel and in compliance with the regulations in force in the country of use.

Any tampering or intervention carried out by unqualified personnel will void the product warranty.

It is recommended to place the device in a dry place protected from atmospheric agents.


TECHNICAL SPECIFICATIONS

FIRE RATING	34 A 183 B
EXTINGUISHING AGENT	100% Green Wave Premix
PROPELLANT	Cartridge with 80 g CO ₂
TEMPERATURE RANGE	+5°C / +60°C
NOMINAL CHARGE	9 Liters
FULL WEIGHT	~ 14,90 Kg
DIMENSIONS	Height 570 (base - valve) +/- 5 mm (with bottom) Diameter (cylinder) 182 +/- 2 mm
DISCHARGE TIME	~ 55,1 seconds
CYLINDER PRESSURE TEST	PT 30 bar
CYLINDER VOLUME	10,78 L
SAFETY DEVICE	Set between 22 and 27 bar
CYLINDER MATERIAL	Alloy steel
TREATMENT	Outside: Sandblast and powder painting, Ral 3000 Inside: Plastic coating

PACKAGING

(Note: quantities and measurements are indicative and can be subject at changes)

STANDARD
Maximum nr. 30 pieces for pallet
(single packaging)
Pallet dimensions 100x120 cm




TRANSPORT DISPOSAL

Land transport : Exemption for the purposes of ADR disposal 594
Ship Transport : IMDG Code – UN 1044 class 2.2 Fire Extinguishers

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
32093-601_GW9A_Technical manual	Technical manual	GW9A_32093-601	08/10/25	S.R.		0	2/3

GW9A 32093-601 : Portable Fire Extinguisher, 9 L Foam

COMPONENTS AND SPARE PARTS LIST



NUM.	DESCRIPTION	CODE
1	Valve M. 74x2	3008
1.1	O-ring valve	0201-5
1.2	Safety device	n.a.
1.3	Safety pin	n.a.
2	Safety pin seal	0285
3	Pressurization cap	3033-2
4	Hose with dispensing nozzle	2297-2V
5	Bursting disk for dip tube	0262-32

NUM.	DESCRIPTION	CODE
6	PVC dip tube with filter	2180-3
7	Cylinder	3010
8	CO ₂ cartridge 80 g	3029-21
9	Label	2247-701
10	Plastic bottom	3028-1
11 OPTIONAL	Wall-mounted bracket for fire extinguisher with clip	3036

The spare part at number 1 includes already all others components indicated from 1.1 to 1.3
 "n.a." mean that the component is not available as single spare part

File name	Type of document	Fire Extinguisher Model	Date	Rele.	Check	Rev.	Pag.
32093-601_GW9A_Technical manual	Technical manual	GW9A_32093-601	08/10/25	S.R.		0	3/3